



AURIGIN® SUMMARY PAGE

(11) Publication number: 02593830 B2

(45) Publication Date: 26 . 03 . 97

Application Publication No.: 04173178 A2

(43) Date of publication of application: 19 . 06 . 92

(51) Int. Cl. 6B41M 5/00

(21) Application number: 02298399

(22) Date of filing: 02 . 11 . 90

(30) Priority: 02 . 11 . 90 JP 298399

(71) Applicant: KANEBO LTD

(72) Inventor: NUNOO TOSHIICHI
KUSAKI KAZUO
ISHIHARA TOSHIHIKO

(54) METHOD FOR PRINTING CLOTH

(57) Abstract:

PURPOSE: To perform the printing of cloth having excellent sharpness, level dyeing properties and fixing properties by pretreating cloth with at least one kind of an agent selected from a water repellent and a softening water repellent and printing the treated cloth by an ink jet system using dye ink containing a hydrotrope agent and subsequently fixing a dye.

CONSTITUTION: At first, cloth such as a fabric, a knitted fabric or a nonwoven fabric is pretreated with a treatment solution (pretreatment agent) having at least

one kind of a water repellent and a softening water repellent dispersed or dissolved therein. Subsequently, a dye is applied to the cloth thus treated by an ink jet system. At this time, when no hydrotrope agent is used in the pretreatment agent, the hydrotrope agent is added to dye ink. The printed cloth is next dried at 80-120°C and a dye is subsequently fixed by the method corresponding to the dye to wash and dry the printed cloth. The hydrotrope agent enhances fixing properties and level dyeing properties and, concretely, urea is generally used.

COPYRIGHT: (C)1992,JPO&Japio